

**THE
WATER
PEOPLE**



Hydromix™

Hydromix Low-Rise (Ambient & Boiling)

HOME PRODUCTS

Countertop Water Filters
Crocks
Under Bench Filter Systems
Reverse Osmosis Purifiers
Shower and Bath filters
Baby and Children
Fridge Filters
e-Tap
Boiling Drinking water
Boiling and Ambient
Drinking Water
Boiling and Chilled
Drinking Water
Faucet Options

OFFICE PRODUCTS

Floor Standing Bubblers
Coolers
Chilled Water
e-Tap
Boiling Drinking water
Boiling and Ambient
Drinking Water
Boiling and Chilled
Drinking Water

TRAVEL PRODUCTS

INDUSTRIAL PRODUCTS



**Natural flow
water -
no time delay**

The HYDROMIX® Low-Rise tap provides you with filtered boiling and ambient water at the turn of a handle. Simply turn the tap handle left and down for filtered boiling water and turn right for filtered ambient water.

The tap is designed to push down to differentiate it from the tap mixer and to provide for its child safe interlock button. Also, as the tap is classified as an under bench system it eliminates the potential for splashing, which is why it is preferred by Occupational Health & Safety personnel in major institutions.

Unlike many taps on the market the HYDROMIX® Low-Rise tap uses the natural flow of the water supply to push the boiling water out of the tap, which eliminates the use of an electrical pump. The water arrives and ceases immediately—no time delay

The Water People

22 High Street,
Glen Iris 3146
Ph: 03 9885 0222
Fax: 03 9885 6541
www.waterpeople.com.au
sales@waterpeople.com.au

Your Clear Choice

THE
WATER
PEOPLE



Hydromix

Hydromix Low-Rise (Ambient & Boiling)

Specifications

- Non-electronic and has no solenoid valve which means no water hammer or costly repairs
- No pump - it works on natural water flow
- No splashing or over-run therefore no scaling or wasted water
- The filter service is based on 4000L of water usage instead of being reliant on a manufacturer programmed light which is often misleading
- Fewer filter changes as it has larger capacity filters
- 5 year pro rata warranty
- Water temperature to 98°C
- Anti-flood design tap
- Child-safe interlock button
- No tundish required
- Optional integral 24 hour 7 day programmable timer
- Worlds best temperature control system, accuracy to $\pm 0.5^{\circ}\text{C}$
- CFC free insulation minimises heat losses and operating costs

Selection Chart

To select the correct size unit for your needs, simply determine how many cups of boiling water are required at any one time, then choose the corresponding model from the chart below.

Model No.	No. of Cups Served	Rating KW.	Cups/h Recovery	Phase / Voltage	Height mm	Width mm	Depth mm
FH 10/2 Ltr	10	1.8	80	1/240	370	195	200
FH 20/4 Ltr	20	2.4	110	1/240	440	195	235
FH 30/6 Ltr	30	2.4	110	1/240	535	195	235
FH 40/8 Ltr	40	2.4	110	1/240	455	330	345
FH 60/12 Ltr	60	2.4	110	1/240	535	330	345

5 year
pro rata
warranty



The Water People


22 High Street,
Glen Iris 3146

Ph: 03 9885 0222

Fax: 03 9885 6541

www.waterpeople.com.au

sales@waterpeople.com.au



Your Clear Choice