

**THE
WATER
PEOPLE**



Waterlux®

DRINKING FOUNTAIN (Colour-Bond)

HOME PRODUCTS

Countertop Water Filters
Cocks
Under Bench Filter Systems
Reverse Osmosis Purifiers
Shower and Bath filters
Baby and Children
Fridge Filters
e-Tap
Boiling Drinking water
Boiling and Ambient
Drinking Water
Boiling and Chilled
Drinking Water
Faucet Options

OFFICE PRODUCTS

Floor Standing Bubblers
Coolers
Chilled Water
e-Tap
Boiling Drinking water
Boiling and Ambient
Drinking Water
Boiling and Chilled
Drinking Water

The Waterlux® Drinking Fountain comes with a bubbler and optional glass filler and is a very sturdy self-contained water cooler designed specifically for the workplace.

These water coolers represent the most modern design available in colour-bond cabinets. Featuring arc-formed panels for superior appearance, the front panel removes for ease of servicing. They are engineered to the highest level of quality and dependability.

Your Waterlux® Drinking Fountain includes:

- Stainless steel reservoir (1.5 litre capacity)
- Industrial grade 304
- Polished stainless steel top
- Front panel that removes for ease of servicing
- Adjustable tamper proof non-squirt bubbler and glass filler
- Cross Flow ventilation
- Adjustable bubbler
- Adjustable levelling feet
- Power indicator light
- Ample provision for internal filtration
- The water lines connect straight to Australian Standard fittings
- 1 year comprehensive warranty
- Optional glass filler



Select the top
style to suit
your needs



The Water People

22 High Street,
Glen Iris 3146
Ph: 03 9885 0222
Fax: 03 9885 6541
www.waterpeople.com.au
sales@waterpeople.com.au

Your Clear Choice



DRINKING FOUNTAIN (STAINLESS STEEL)

Dimensions:

height 1100mm (Bubbler only), width 350mm x depth 350mm

Weight:

M2/M3 - 26kgs, M4/M5 - 28kgs, M10/M11 - 30kgs

Water connections:

Mains pressure inlet is ½" female BSP fitting. Drain outlet is a 40mm female F.P.V.C. pipe. The water supply and drain connections are factory supplied.

Voltage:

240V, 50Hz single phase. A 2 metre house cable and 3 pin plug is supplied.

Cooling system (Chilling Tank):

Combination tube tank type. Tank is stainless steel and can hold up to 1.5 litres with copper coils bonded around the outside, which offers maximum cooling efficiency. Double wall separation is provided between refrigerant and drinking water and the evaporator tank is fully insulated.

M2/M3 - Uses 250gms of R134A refrigerant

M4/M5 - Uses 190gms of R134A refrigerant

M10/M11 - Uses 127 gms of R22 refrigerant

Water flow controls:

The bubbler is rated to supply 1.7litres per minute at mains water pressure of between 140 and 700kPa. An automatic, self-regulating control is fitted to overcome varying mains pressure.

Compressors:

M2/M3 - 1/8 h.p. capacity 138 watts

M4/M5 - 1/5 h.p. capacity 230 watts

M10/M11 - 1/4 h.p. capacity 430 watts

Performance to ARI 1010-94 standard:

Water Inlet - 26.7°C, Water Outlet - 10°C, Ambient Air - 32.2°C

Thermostat: Factory pre-set. It is adjustable but tamperproof. A remote sensing bulb provides accurate temperature control of cold water.

Warranty: 1 year warranty extended to 5 years if water filters connected and recommended servicing carried out by The Water People.

Also available
in stainless steel
side panels



The Water People

22 High Street,

Glen Iris 3146

Ph: 03 9885 0222

Fax: 03 9885 6541

www.waterpeople.com.au

sales@waterpeople.com.au

Room Temp	Water Temp	Litres per Hour
21°	15°	22
27°	21°	19
27°	27°	14
27°	32°	11
32°	21°	18
32°	27°	13
32°	32°	10

Your Clear Choice

Kevro Enterprises Pty Ltd T/as A.B.N. 77 476 448 813